


**For fire rated 2" frames
with 1/2" drywall penetration.**

NEW!



Strike depth: 1-3/8"

The 4500 is the first electric strike designed for installation in 2" UL 10C fire rated frames with the 1/2" drywall penetration. Based on the design of the popular 5000 series, the new 4500 electric strike features a low profile 1-3/8" depth, heavy duty cast stainless steel construction and horizontal adjustment for simple installation. The 4500 takes "heavy duty" to the next level. Its strength is derived from a unique keeper pin locking design, enabling the 4500 to exceed the ratings of the frame, door and locking hardware. The 4500 electric strike... another first from HES.

The 4500 is the solution for virtually every cylindrical and offset mortise lockset application.

Available September 2003

Specifications

- NFPA 252, ASTM E152

Standard Features

- Heavy duty stainless steel construction
- Forcing strength rating 3,000 lbs
- Cycle rating 1,000,000 operations
- Designed for use with up to 3/4" cylindrical locksets and offset mortise locks
- 1-3/8" depth - for installation in 2" frames with 1/2" dry-wall penetration
- Dual voltage 12/24 VDC
- Fail secure standard
- Five year warranty

Electrical

- .24 Amps @ 12VDC
- .12 Amps @ 24VDC

Optional Features

- Optional fail safe version available
- Adjustable deadlatch tab accommodates various mortise locks
- Optional LBM/LBSM - Latchbolt/strike monitoring on select models

Finishes

- 605 Bright brass
- 606 Satin brass
- 612 Satin bronze
- 613 Bronze toned
- 630 Satin stainless steel (standard)
- 651 Polished chrome