

9500 Genesis II™
The fire rated, completely
surface mounted electric strike

NEW!



A classic example of one good thing leading to another, the 9500 Genesis II™ is the fire rated version of its 9600 predecessor. Like the 9600, the 9500 Genesis II™ is completely surface mounted, featuring all components completely encased within its 3/4" thick stainless steel housing--requiring no cuts to the jamb. Designed for use with 3/4" exit devices, the Genesis series are field selectable to either fail secure or fail safe operation and can be operated with either 12 or 24 Volts DC. The 9500 Genesis II™ is UL 10C fire and Warnock Hersey rated, making it the perfect solution for fire rated rim exit applications.

Available October 2003

Specifications

- NFPA 252, ASTM E152
- UL 10C fire rated
- UL 305 listed
- Warnock Hersey UBC7-297, UBC7-294

Standard Features

- Completely surface mounted
- Heavy duty - designed for use with 3/4" exit devices
- Dual voltage 12/24VDC
- Field selectable fail secure/fail safe
- Forcing strength rating 1,900 lbs.
- Cycle rating 1,000,000 operations
- Five year warranty

Electrical

- .12 Amps @ 24VDC
- .24 Amps @ 12VDC

Optional Features

- Optional LBM/LBSM - Latchbolt/strike monitoring on select models

Finishes

- 605 Bright brass
- 606 Satin brass
- 612 Satin bronze
- 613 Bronze toned
- 630 Satin stainless steel (standard)
- 651 Polished chrome