

Completely surface-mounted, the 9600 Genesis™ is the first of its kind. The 9600 accommodates rim exit devices in metal or wood jambs. The 9600 features an internally mounted solenoid and two stainless steel independently operating locking mechanisms. The 9600 is easy to install, with all components of the 9600 encased in the 9" x 1-3/4" x 3/4" faceplate, requiring no cuts to the jamb prior to installation.

#### *Standard Features*

- Patent #6,390,520
- Dual locking
- Tamper resistant - heavy duty construction
- Internally mounted solenoid
- Field selectable fail secure/fail safe
- Accommodates up to a 3/4" throw pullman latch
- Non-handed
- Includes horizontal lockdown screws
- 5 year limited warranty

#### *Electrical*


- .45 Amps @ 12VDC
- .25 Amps @ 24VDC

#### *Optional Features*


- LBM - Latchbolt monitor
- LBSM - Latchbolt strike monitor
- 9600-108 - Spacer plate
- 2001 - Plug-in bridge rectifier
- 2005 - SMART Pac II™ power controller
- 2505 - Power Punch™ power supply
- 2006P - Plug-in buzzer
- 2009P - Plug-in L.E.D.

#### *Finishes*

- 605 Bright brass
- 606 Satin brass
- 612 Satin bronze
- 613 Bronze toned
- 630 Satin stainless steel (standard)
- 651 Polished chrome



*type of lock released*



ANSI/BHMA #E09311